



THE GRIPPER GASKET™ SUBMITTAL



Part

- A = Stainless Steel
- B = SBR
- C = Nominal Pipe Size
- D = USA
- E = Gripper Gasket™

Gripper Gasket™ Suggested Specification

Gripper Gasket™ 3" - 24":

Joint restraint for ductile iron water systems including pipe, valves and fittings shall be accomplished using integral boltless restraining gaskets. Pressure rating 350 psi. These gaskets shall be designed, manufactured and tested in accordance with AWWA C111/A21.11. Certified to NSF/ANSI 61. UL Recognized Component. Boltless restraining gaskets shall be Gripper Gasket™ or equivalent.

MADE IN THE U.S.A. , ARRA 2009 "Buy American" Provisions Buy America, 49 CFR 661.1 Requirements

American Recovery Reinvestment Act (ARRA) Section 1605 & Buy America, 49 CFR 661.1 Requirements

Gripper Gaskets are manufactured in the United States of America as required by section 1605 of the American Recovery Reinvestment Act of 2009. We take great pride in manufacturing only top quality "Made in the U.S.A." gaskets.

Gripper Gasket LLC products are made in accordance with Buy America, 49 CFR 661.1, et. seq. All of the components of our product are of U.S. origin. A component is considered of U.S. origin if it is manufactured in the United States, regardless of the origin of its subcomponents. Gripper Gaskets are certified to NSF/ANSI Standard 61 by NSF International.

Gripper Gasket LLC cannot certify that accessories used with our products, such as pipe, valves, fittings, gauges, instrumentation or like components are made in the U.S.A. We pledge to encourage the use of products made in the U.S.A.